

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

## 1. Identification

| Product Name:       | Phenopatch Elastomeric Smooth Patch Gun<br>Grade   | Revision Date:                             | 4/12/2022   |
|---------------------|--|--|---|
| Product UPC Number: | 070798122741   | Supercedes Date:                           | 12/29/2021  |
| Manufacturer:       | Phenomenol Brands<br>Phenopatch Products<br>A Division of DAP Global Inc.<br>2400 Boston Street Suite 200<br>Baltimore, MD 21224-4723<br>410-779-3265 (non - emergency matters)<br>SDS Coordinator: MSDS@dap.com<br>Emergency Telephone: 1-800-535-5053,<br>1-352-323-3500, 1-800-222-1222 | Product Use/Class:<br>SDS No:<br>Preparer: | Caulking Compound<br>7994905<br>Regulatory and Environmental<br>Affairs |

## 2. Hazards Identification

EMERGENCY OVERVIEW: Under normal use conditions, this product is not expected to cause adverse health effects.

GHS Classification STOT RE 2

### Symbol(s) of Product



Signal Word Warning

Possible Hazards 62% of the mixture consists of ingredients of unknown acute toxicity SAP Number:

#### GHS HAZARD STATEMENTS

STOT, repeated exposure, category 2 H373 May cause damage to organs through prolonged or repeated exposure.

| GHS LABEL PRECAU | JTIONARY STATEMENTS |
|------------------|---------------------|
| D260             | Do not broo         |

| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
|------|--|
| P314 | Get medical advice/attention if you feel unwell. |
| P501 | Dispose of contents/container.                   |

## 3. Composition/Information on Ingredients

| Chemical Name                         | CAS-No.                            | <u>Wt. %</u> | GHS Symbols         | GHS Statements |
|---------------------------------------|------------------------------------|--------------|---------------------|----------------|
| Limestone                             | 1317-65-3                          | 45-70        | No Information      | No Information |
| Stoddard solvent                      | 8052-41-3                          | 0.5-1.5      | GHS08               | H304-372       |
| The text for GHS Hazard Statements sl | nown above (if anv) is given in th | e "Other in  | formation" Section. |                |

## First-aid Measures

FIRST AID - INHALATION: Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: In case of contact, wash skin immediately with soap and water.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

## 5. Fire-fighting Measures

### UNUSUAL FIRE AND EXPLOSION HAZARDS: None Known.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog, Water

## 6. Accidental Release Measures

ENVIRONMENTAL MEASURES: Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate. Dispose of saturated absorbent or cleaning materials appropriately. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

### 7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDRENIDO NOT TAKE INTERNALLY. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling.

STORAGE: Avoid excessive heat and freezing. Do not store at temperatures above 120 °F (49 °C). Store away from caustics and oxidizers.

## 8. Exposure Controls/Personal Protection

| Ingredients with Occupational Exposu<br>Chemical Name | re Limits<br>ACGIH TLV-TWA | ACGIH-TLV STEL | <u>OSHA PEL-TWA</u>   | OSHA PEL-CEILING |
|---|----------------------------|----------------|---|------------------|
| Limestone   | N.E.                       | N.E.           | 15 mg/m3 TWA<br>total dust, 5 mg/m3<br>TWA respirable<br>fraction |                  |
| Stoddard solvent                                      | 100 ppm TWA                | N.E.           | 500 ppm TWA,<br>2900 mg/m3 TWA                                    | N.E.             |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

### **Personal Protection**



RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.



SKIN PROTECTION: Rubber gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



HYGIENIC PRACTICES: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

## 9. Physical and Chemical Properties

| Appearance:<br>Odor:<br>Density, g/cm3:<br>Freeze Point, °C:<br>Solubility in Water:<br>Decomposition Temperature,<br>Boiling Range, °C:<br>Minimum Flash Point, °C:<br>Evaporation Rate:<br>Vapor Density:<br>Combustible Dust: | °C: | White to Off<br>Very Slight J<br>1.66 - 1.66<br>Not Establis<br>Not Establis<br>100 - 100<br>100<br>Slower That<br>Heavier That<br>Does not su |
|--|-----|--|
| Combustible Dust.  |     | Does not su  |

White to Off-White Very Slight Ammonia 1.66 - 1.66 Not Established Not Established Not Established 100 - 100 100 Slower Than n-Butyl Acetate Heavier Than Air Does not support combustion Physical State: Odor Threshold: pH: Viscosity (mPa.s): Partition Coeff., n-octanol/water: Explosive Limits, %: Auto-Ignition Temperature, °C Vapor Pressure, mmHg: Flash Method: Flammability, NFPA: Paste Not Established Between 7.0 and 12.0 Not Established Not Established Not Established Not Established Seta Closed Cup Non-Flammable

(See "Other information" Section for abbreviation legend) (If product is an aerosol, the flash point stated above is that of the propellant.)

# 10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

## 11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Under normal use conditions, this product is not expected to cause adverse health effects. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Under normal use conditions, this product is not expected to cause adverse

#### health effects. Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury.

#### CARCINOGENICITY: No Information

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Repeated or prolonged exposure may cause mild irritation of eyes and skin. Constituents of this product include crystalline silica which ,if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

#### PRIMARY ROUTE(S) OF ENTRY: Skin Contact

#### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

| <u>CAS-No.</u> | <u>Chemical Name</u> | <u>Oral LD50</u> | Dermal LD50        | <u>Vapor LC50</u> |
|----------------|----------------------|------------------|--------------------|-------------------|
| 1317-65-3      | Limestone            | 6450 mg/kg Rat   | N.I.               | N.I.              |
| 8052-41-3      | Stoddard solvent     | >7000 mg/kg Rat  | >2000 mg/kg Rabbit | 21 mg/L Rat       |

N.I. = No Information

## 12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

## 13. Disposal Information

**DISPOSAL INFORMATION:** This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

## 14. Transport Information

| DOT UN/NA Number:                                | N.A.               |
|--|--------------------|
| DOT Proper Shipping Name:<br>DOT Technical Name: | Not Regulated N.A. |
| DOT Hazard Class:                                | N.A.               |
| Hazard SubClass:<br>Packing Group:               | N.A.<br>N.A.       |

## 15. Regulatory Information

## U.S. Federal Regulations:

### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Specific target organ toxicity (single or repeated exposure)

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt. This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

| Revision Date:                      | 4/11/20       | )22  | Supersedes Date: 12/29/2021 |
|-------------------------------------|---------------|--|-----------------------------|
| Reason for revision:                | 01 - Pi       | nce and/or Product Properties C<br>roduct Information<br>xposure Controls/Personal Prote | 3                           |
| Datasheet produced<br>HMIS Ratings: | by:           | Regulatory Department  |                             |
| Health:                             | Flammability: | Reactivity:  | Personal Protection:        |
| 1                                   | 0             | 0  | Х                           |

- VOC Material, g/L: 38
- VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 1.50
  - VOC Actual, Wt/Wt%: 2.3

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

- H304 May be fatal if swallowed and enters airways.
- H372 Causes damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:





Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.