



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® POWER POINT® 230 Premium Elastomeric Acrylic Latex Sealant

### PRODUCT DESCRIPTION

**DAP® POWER POINT® 230 PREMIUM ELASTOMERIC ACYRYLIC LATEX SEALANT** is specifically formulated for demanding interior and exterior applications. It delivers excellent adhesion & flexibility for a durable, crack-proof seal that is waterproof and weatherproof. It is easy to apply and tool and is paintable in just 30 minutes. It provides a waterproof and tight seal that is mold and mildew resistant once cured. 60 Year. Meets ASTM Specification C920, Class 12.5. Interior/exterior use.



PACKAGING	COLOR	UPC
10.1 fl oz (300 mL) Cartridge	White	7079818800

### KEY FEATURES & BENEFITS

- 60 Year
- Stays flexible
- Crackproof
- Waterproof & weatherproof
- Paintable in 30 minutes
- Easy water clean-up
- Low odor
- Cured sealant is mold & mildew resistant
- Meets ASTM C920, Class 12.5
- VOC compliant
- Interior/exterior use

### SUGGESTED USES



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## USE FOR CAULKING & SEALING:

- Windows
- Doors
- Siding
- Trim
- Molding
- Pipes
- Vents
- Corner Joints
- Butt Joints
- Tuck Pointing
- Other gaps & cracks, especially prior to painting

## ADHERES TO:

- Wood – painted & unpainted
- Aluminum
- Most metals
- Vinyl
- Most plastics
- Plaster
- Drywall
- Glass
- Fiber Cement
- Stucco
- Composite
- PVC trimboard
- Brick
- Stone
- Concrete
- Mortar
- Most common building materials

## FOR BEST RESULTS

- Apply in temperatures between 40°F to 100°F.
- Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temperatures and higher humidity will slow down dry time.
- Not for continuous underwater use or filling surface defects.
- Joint size should not exceed 1/2" wide x 1/2" deep. If joint depth exceeds 1/2", use backer rod material.
- Store sealant away from extreme heat or cold.

## APPLICATION

### Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material.

### Product Application

1. Apply in temperatures above 40°F. Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temperatures and higher humidity will slow down dry time.
2. Cut nozzle at 45° angle to desired bead size.
3. Load cartridge into caulk gun.
4. Fill gap or joint with sealant.
5. If necessary, tool or smooth the bead of sealant with a finishing tool before sealant skins over.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

6. Clean up excess wet sealant with a damp sponge before it skins over. Excess dried sealant must be cut or scraped away.
7. Allow sealant to dry 30 minutes (longer in cool or humid conditions) before painting with latex or oil-based paints.
8. Reseal cartridge for storage and reuse.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Gunnable, non-sag paste
Base Polymer	Advanced acrylic polymer
Filler	Calcium carbonate
Volatile	Water
Weight % Solids	80
Density (lbs per gallon)	12.9
Odor	Very mild
Clean Up	Water
Flash Point	>212°F
Freeze Thaw Stability (ASTM C1183)	Passes 5 cycles
Shelf Life	12 months
Coverage	10.1 fl oz cartridge: Up to 55 linear ft. at a 3/16" bead size
Typical Application Properties	
Application Temperature Range	40°F to 100°F
Tooling Time (Working Time)	10 minutes*
Tack Free Time	30 minutes*
Full Dry Through	24 hours*
Return to Service Time	24 hours*
Vertical Sag (ASTM D2202)	0.05"
Typical Cured Performance Properties	
Service Temperature Range	-30°F to 180°F
Paint Ready Time	30 minutes*
Water Ready Time	24 hours*
Mildew Resistance	Dried caulk is mold & mildew resistant



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Dynamic Joint Movement (ASTM C719)	+/- 12.5%
------------------------------------	-----------

*Dependent on temperature and humidity	
--	--

## CLEAN UP & STORAGE

Clean up excess wet caulk with a damp sponge before it skins over. Excess dried caulk must be cut or scraped away. Clean hands and tools with warm water and soap. Reseal cartridge and store in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS sheet by visiting our website at [dap.com](http://dap.com) or calling 888-DAP-TIPS.

## LIMITED WARRANTY

**WARRANTY:** If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**